

Communicate.



Utilize the Power of Full Color for Dynamic Advertising.



TRUCOLOR™ SERIES

State-of-the-Future Full Color LED Displays.

Three powerful resolutions (16, 20, and 23mm) available to fit any application in today's market.



Sharp

With equal spacing of the red, green, and blue LEDs, and access to 4 Billion colors, pictures and video graphics are fluid and sharp.

Durable

IP65 rated aluminum construction means sealed lightweight cabinets that allow no outside contaminants or water. Light gray cabinets allow for no ventilation and low internal heat. Important factors that preserve the life of the display.

Smart

Modular design, with access from the front, with simple external power and data connections, allows for quick and easy service, if needed, by anyone.

Professional Support

Project management, 24 hr tech support, on-site training, in-house content management team, and our exclusive Total Support (featuring our Virtual Buddy System, VBS) ensures that your display will always be effective with dynamic advertising.



S P E C I F I C A T I O N S



- LEDs Per Pixel: 1 Red, 1 Green, 1 Blue
- 140° Viewing Angle
- Borderless
- 7" Depth
(Plus 3" Steel Mounting Angle)
- Ventless Sealed Aluminum Cabinet
- IP65 Rated
- ETL Listed Mark

Model	Pixel Matrix	Height	Width	Weight (per side)	Power (amps per side)
621-5	48 x 128	2'-7"	6'-10"	192 lbs	7
624-5	48 x 144	2'-7"	7'-8"	216 lbs	8
626-5	48 x 160	2'-7"	8'-6"	240 lbs	9
821-5	64 x 128	3'-5"	6'-10"	256 lbs	9
824-5	64 x 144	3'-5"	7'-8"	288 lbs	10
826-5	64 x 160	3'-5"	8'-6"	320 lbs	11
1021-5	80 x 128	4'-3"	6'-10"	320 lbs	11
1024-5	80 x 144	4'-3"	7'-8"	360 lbs	13
1026-5	80 x 160	4'-3"	8'-6"	400 lbs	14
1221-5	96 x 128	5'-1"	6'-10"	384 lbs	14
1224-5	96 x 144	5'-1"	7'-8"	432 lbs	15
1226-5	96 x 160	5'-1"	8'-6"	480 lbs	17

Windows-Based PC Messaging and Scheduling Software, Temperature Probe, and 54Mbps/2.4 Ghz Wireless Transmission Included (Ethernet Bridge). 7 Year Warranty and 24 Hour Tech Support.



- LEDs Per Pixel: 1 Red, 1 Green, 1 Blue
- 140° Viewing Angle
- Borderless
- 7" Depth
(Plus 3" Steel Mounting Angle)
- Ventless Sealed Aluminum Cabinet
- IP65 Rated
- ETL Listed Mark

Model	Pixel Matrix	Height	Width	Weight (per side)	Power (amps per side)
621-6	48 x 128	3'-3"	8'-6"	360 lbs	13
624-6	48 x 144	3'-3"	9'-6"	405 lbs	15
626-6	48 x 160	3'-3"	10'-7"	450 lbs	16
821-6	64 x 128	4'-3"	8'-6"	480 lbs	17
824-6	64 x 144	4'-3"	9'-6"	540 lbs	19
826-6	64 x 160	4'-3"	10'-7"	600 lbs	22
1021-6	80 x 128	5'-4"	8'-6"	420 lbs	23
1024-6	80 x 144	5'-4"	9'-6"	472 lbs	25
1026-6	80 x 160	5'-4"	10'-7"	575 lbs	28
1221-6	96 x 128	6'-4"	8'-6"	503 lbs	27
1224-6	96 x 144	6'-4"	9'-6"	567 lbs	31
1226-6	96 x 160	6'-4"	10'-7"	630 lbs	34

Windows-Based PC Messaging and Scheduling Software, Temperature Probe, and 54Mbps/2.4 Ghz Wireless Transmission Included (Ethernet Bridge). 7 Year Warranty and 24 Hour Tech Support.



- LEDs Per Pixel: 1 Red, 1 Green, 1 Blue
- 140° Viewing Angle
- Borderless
- 7" Depth
(Plus 3" Steel Mounting Angle)
- Ventless Sealed Aluminum Cabinet
- IP65 Rated
- ETL Listed Mark

Model	Pixel Matrix	Height	Width	Weight (per side)	Power (amps per side)
616-7	48 x 96	3'-8"	7'-4"	270 lbs	11
618-7	48 x 112	3'-8"	8'-6"	315 lbs	13
621-7	48 x 128	3'-8"	9'-9"	360 lbs	15
624-7	48 x 144	3'-8"	10'-11"	405 lbs	17
626-7	48 x 160	3'-8"	12'-2"	450 lbs	19
816-7	64 x 96	4'-11"	7'-4"	360 lbs	15
818-7	64 x 112	4'-11"	8'-6"	420 lbs	18
821-7	64 x 128	4'-11"	9'-9"	480 lbs	20
824-7	64 x 144	4'-11"	10'-11"	540 lbs	23
826-7	64 x 160	4'-11"	12'-2"	600 lbs	25
1016-7	80 x 96	6'-1"	7'-4"	450 lbs	23
1018-7	80 x 112	6'-1"	8'-6"	525 lbs	27
1021-7	80 x 128	6'-1"	9'-9"	600 lbs	31
1024-7	80 x 144	6'-1"	10'-11"	675 lbs	35
1026-7	80 x 160	6'-1"	12'-2"	750 lbs	39

Windows-Based PC Messaging and Scheduling Software, Temperature Probe, and 54Mbps/2.4 Ghz Wireless Transmission Included (Ethernet Bridge). 7 Year Warranty and 24 Hour Tech Support.